


Wire terminals are used to easily connect wires to screws, posts, and other terminals/wires. They are available in a variety of wire gauges and connection types. Remington Industries offers a wide variety of wire terminals to help you make clean, convenient terminations between wires in your project; take a look at the chart below to see what we offer. The tin-plated copper or brass base of these terminals provides good electrical connectivity while also allowing for a quick, solderless crimp connection. Additionally, on insulated terminals, PVC insulation protects the connection against abrasion, chemicals, oils, fuels, and solvents.

Our wire terminals are available in different wire sizes (see table below) and sometimes varying stud sizes (see table below). We also offer the terminals in packages of 10 pieces or 100 pieces for your convenience. Remington Industries is also glad to provide **Custom Wire Services**: We can find and add most wire terminals to a wire/cable of your choice so that it is ready for your project straight out of the box. Feel free to [contact Remington Industries](#) if you would like our assistance.


- See table below for specifications by terminal type
- Termination Type: Crimp
- Package Quantities Available: x10 pieces or x100 pieces




FORK TERMINAL




RING TERMINAL



QUICK CONNECT (MALE) TERMINAL



QUICK CONNECT (FEMALE) TERMINAL



BUTT TERMINAL

PART NUMBER	TERMINAL TYPE	WIRE SIZE	CURRENT RATING	TEMPERATURE RATING	STUD SIZES AVAILABLE	TERMINAL MATERIAL	INSULATION MATERIAL
SVS2	Fork	14 to 16 AWG	27 A	75°C (167°F)	#6, #8, #10	Tin-Plated Copper	Blue PVC
SVS1.25	Fork	16 to 22 AWG	19 A	75°C (167°F)	#6, #8, #10	Tin-Plated Copper	Red PVC
RVS2	Ring	14 to 16 AWG	27 A	75°C (167°F)	#6, #8, #10	Tin-Plated Copper	Blue PVC
RVS1.25	Ring	16 to 22 AWG	19 A	75°C (167°F)	#6, #8, #10	Tin-Plated Copper	Red PVC
BV2	Butt / Splice	14 to 16 AWG	27 A	75°C (167°F)	N/A	Tin-Plated Copper	Blue PVC
BV1.25	Butt / Splice	16 to 22 AWG	19 A	75°C (167°F)	N/A	Tin-Plated Copper	Red PVC
MDD2-250	Quick Connect, Male	14 to 16 AWG	15 A	75°C (167°F)	N/A	Tin-Plated Brass	Blue PVC
MDD1.25-250	Quick Connect, Male	16 to 22 AWG	10 A	75°C (167°F)	N/A	Tin-Plated Brass	Red PVC
FDD2-250	Quick Connect, Female	14 to 16 AWG	15 A	75°C (167°F)	N/A	Tin-Plated Brass	Blue PVC
FDD1.25-250	Quick Connect, Female	16 to 22 AWG	10 A	75°C (167°F)	N/A	Tin-Plated Brass	Red PVC
SC35	Lug	2 AWG	36 A	160°C (320°F)	5/16", 3/8"	Tin-Plated Copper	None
SC25	Lug	4 AWG	36 A	160°C (320°F)	5/16", 3/8"	Tin-Plated Copper	None

Wire Terminals Fork, Ring, Butt, Quick Connect, & Lug Data Sheet

Remington Industries is proud to offer our Custom Wire Services

Our exclusive inventory of in-stock wire and ability to procure wire of all kinds makes us the perfect partner for wire purchasing and custom wire services. We are proud to provide essential, high quality wire for engineering projects, educational science projects, coil winding, and electronics applications.

Some of our many wire services include the following:

- Wire Re-Packaging
- Bifilar & Trifilar Windings
- Wire Processing
- Coil Winding
- Wire Procurement Services

If you have any questions or need any information about our [Wire Services](#), feel free to contact us! It only takes one call to get experienced assistance.

Contact us by phone:
[\(815\) 385-1987](tel:(815)385-1987)

Contact us by email:
sales@remingtonindustries.com

DATE | ISS. | REVISION | BY

Drawn by: AG 1/31/20
Drawing rev.: --

Remington
Industries

3521 N. Chapel Hill Rd
Johnsburg, IL 60051 USA
remingtonindustries.com