



## C721U221KSYDCAWL35

C700KJN SFTY X1-440 Y1-400, Ceramic, 220 pF, 10%, 440 VAC (X1), 400 VAC (Y1), Y5P, 10mm





The measurement position of Lead Spacing (S) and Width (V) is critical in straight lead capacitors.

Click here for the 3D model.

Dimensions	
D	9mm MAX
Т	6mm MAX
S	10mm MAX
LL	3.5mm +/-1mm
F	0.6mm +/-0.1mm
V	2.7mm +/-0.5mm

Packaging Specifications	,
Packaging	Bulk, Bag
Packaging Quantity	500

General Information		
Series	C700KJN SFTY X1-440 Y1-400	
Style	Radial Disc	
RoHS	Yes	
Termination	Tin	
Failure Rate	N/A	
Qualifications	TUV, UL, cUL	
AEC-Q200	No	

Specifications			
Capacitance	220 pF		
Capacitance Tolerance	10%		
Voltage AC	440 VAC (X1), 400 VAC (Y1)		
Temperature Range	-40/+125°C		
Temperature Coefficient	Y5P		
Dissipation Factor	2.5% 1 kHz 5.0Vrms		
Insulation Resistance	10 GOhms		
Safety Class	X1/Y1		
Dielectric Withstanding Voltage	4000 VAC		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.