


# DA-DFN8-2X2P50

DFN-8 TO DIP ADAPTER – 2mm x 2mm – P0.50



This adapter breaks out the pins of a DFN-8 component (with a body of 2mm x 2mm and 0.50mm pin pitch) into a board with 0.1" (2.54mm) spaced pins.

This is a high quality PCB, with all the copper pads and contacts plated with Electroless Nickel Immersion Gold (ENIG) process, offering an excellent surface planarity and oxidation resistance.


The land pattern includes a central pad that can be used to dissipate heat from a high-power integrated circuit, like a motor controller or an audio amplifier. There is also a hole drilled through the central pad that can be used to drop some solder and ensure dissipation and conductivity up to the component. The central pad is connected to a dedicated outer pad, allowing to eventually wire a connection to it.

Specifications	
Supported packages	DFN-8
Package body size	2mm x 2mm
Component pin pitch	0.50mm
Board pin pitch	2.54mm (0.1")
Temperature rating	-25°C to +125°C
Material	FR4
RoHS compliant	Yes

## Board dimensions

All dimensions are in millimeters

**DFN-8**  
**Body: 2x2**  
**Pitch: 0.50**



## Land pattern dimensions

All dimensions are in millimeters

**DFN-8**  
**Body: 2x2**  
**Pitch: 0.50**

