## TRANSFORMING TECHNOLOGIES

**OUTSTANDING ALTERNATIVES IN STATIC CONTROL** 


#### MT3500 Series Textured Two Layer ESD Table Mat

# Protect your sensitive items as well as your work surface with durable ESD matting.

The MT4000 Textured series ESD-safe 2-layer rubber matting is made of 100% co-extruded rubber. The durable two layer mat is constructed with a textured dissipative top layer and a conductive bottom layer and offers excellent resistance to hot solders, soldering irons and most solvents.

MT4000 is available in 0.080" thick rolls or cut mats. Cut mats are packaged individually with 10mm snaps and a common point ground cord. Full rolls are 40ft long and can be easily cut with a utility knife to fit your unique workstation. Available in nasa blue, royal blue, green and gray colors.

Meets or exceeds the requirements of ANSI ESD S20.20 per test method ANSI/ESD STM4.1



#### Features

- Textured, Non-Slip 2 Layer Rubber
- ESD Properties: 10^6-10^8 Rtt
- Excellent Resistance to Hold Solders, Soldering Irons and Most Solvents
- Available in 40ft rolls or an Assortment
  - of Ready Made Table Mats .
- Nasa Blue, Royal Blue, Green, and Gray

#### **Applications:**

Creates an ESD safe work area by a providing a path-to-ground for electrical charges as well as protecting the work surface from damage.

Specifications: Color Blue, Roval Blue, Green, Grav		Part Numbers:	Part Numbers:
Texture Gauge Tensile Elongation Tear	Blue, Royal Blue, Green, Gray Yes 0.080" 350 lb/in2 minimum 110% minimum 80 lb/in minimum	Full Rolls MTT3524B Roll Mat, Blue, 24"x 40"x .080" MTT3530B Roll Mat, Blue, 30"x 40"x .080" MTT3536B Roll Mat, Blue, 36"x 40"x .080" MTT3548B Roll Mat, Blue, 48"x 40"x .080"	Cut Mats* MTT2436B Mat, 24" x 36"x .080", Hardware MTT2448B Mat, 24" x 48"x .080", Hardware MTT2460B Mat, 24" x 60"x .080", Hardware MTT2472B Mat, 24" x 72"x .080", Hardware
Surface Resistance Top layer Bottom layer RTGP RTT	<10^7ohms <10^4 ohms 5x10^7 to 5x10^8 ohms 5x10^7 to 6x10^8 ohms	Replace "B" at the end of the part number with "RB" for royal blue, "GN" from green or "GY" for gray	MTT3648B Mat, 36" x 48" x .080", Hardware MTT3672B Mat, 36" x 72" x .080", Hardware Shipping Dimensions and Weights
Decay Rate Environmental Testing Conditions:	5kv to 50v in less than .1 sec. 12% RH Temp: 23C	Meets or exceeds requirements of ANSI ESD S4.1. Meets the Federal Standard 101 Method 4046 for static decay. ROHS Compliant	Roll, 24"x40': 55lbs - 25"x 9"x 9"   Roll, 30"x40': 69lbs - 31"x 9"x 9"   Roll, 36"x40': 90lbs - 37"x 9"x 9"   Roll, 48"x40': 111lbs - 49"x 9"x 9"

This document is prepared for our customers as a service, and is to the best of our knowledge true and accurate. However, it is understood and agreed by the users of this document that we will accept no liability for the conclusions reached. Users of this document may therefore wish to perform additional testing before determining that products mentioned are suitable.

### www.transforming-technologies.com

#### 3719 King Road Toledo Ohio 43617 Phone: 419-841-9552 info@transforming-technologies.com

Matting

Rev: 2023-10-04