



PIN ASSIGNMENT		
P1	RED	P2
1	WHTIE	1
2		2
3	SPIRAL	3

Electrical test:
 1.100% short,open,miswire test
 2.Conduct resistance:2 ohm(max)
 3.Insulation resistance:1Mohm(min)
 4.Dielectric test:DC 300V/10ms

NO.	NAME	Q'TY	SPECIFICATION
⑥	TIE	1	BLACK L=80mm
⑤	TUBE	2	HEAT SHRINK TUBE BLACK OD1.5*L15mm.
④	PE BAG	1	CLEAR SIZE:100*200*0.05mm PRINT BLACK"MADE IN CHINA".
③	OUT JACKET	5.5g	OUTER MODEL PVC 45P COLOR BLACK
②	CONN	2	3.5ST MALE Tray6.0mm L=30mm MOLD TYPE NI-PLATED INSULATOR COLOR:BLACK
①	CABLE	1	NOUL 28AWG(7/0.12 TC)*2C(RED,WHITE)+S(43/0.12 TC) JACKET BLACK OD:3.0MM

1PC/PE BAG

RoHS compliant
 Unit: mm

Scale	Free				Date	Name	Customer-No.
TOLERANCE					Drawn	20.02.2017	Amy
					Approved	28.06.2020	Luca
							ASSMANN WSW-No. AK203/MM
DIM	TOL	①	Change shape of overmold	28.06.2020	Luca	Drawing-No. ASS 7886 CA	
		②	Drawn	20.02.2017	Amy	rev01	
Angle	TOL	Id.	Modification	Date	Name	Replace	Sheet

