



Screw Terminal Blocks

2000/12 DS

Order Info

reference number (ref. no.)	128312
PU	20
EAN	4028012106585



Type

Type	Terminal Block
connection type	screw
number of poles	12 pole
colour	naturalal
wire protection	yes

Electrical Data

rated voltage	500 V
rated current	76 A

Connection Data

cross-section rating	16.0 mm ²
cross-section rating (UL)	14-6 AWG
clamping range	0.5 - 22.0 mm ²
type of conductor	fine stranded, stranded, solid
stripping length	10.0 - 10. mm
fixing	Screw
clamping units per pole	1
contact screw assembly	1.0 x 5.5 / \cup 2.0 Nm
mounting hole diameter	4.3 mm
socket diameter	5.40 mm
pin spacing	14.5 mm

Ambient Conditions

T _{max} ambient air (at rated current)	85 °C
T _{min} ambient air (operation)	-40 °C

Materials

insulator material	PA
contact material	brass

flammability rating acc. to UL 94	V-2
------------------------------------------	-----

Approvals

acc. to EN 60998	yes
-------------------------	-----

acc. to UL	yes
-------------------	-----

acc. to CSA	yes
--------------------	-----

Accessories

2000 BZ/12	191812
-------------------	--------

ZEL 110	196420
----------------	--------
