FlexCore[™] 150mm, 300mm, 600mm Doors



specifications

The 150mm, 300mm and 600mm Doors are front single hinged doors that mount on either side of the FlexCore™ Optical Distribution Frame (ODF), protecting installed trunk cables and assemblies. Lift off hinges allow doors to be added and removed in the field with ease.



key features and benefits

		FDUFD1545S*GY	FDUFD3045*GY	FDUFD6045P*GY
Feature	Benefit	150mm	300mm	600mm
Key-lockable door handle	Enhanced security	x	х	X
80% open perforation pattern	Showcases fiber infrastructure while maintaining access security	_	_	х
Integrated electrical bonding	Simplifies system grounding	Х	Х	х
Hinge kit	Allows door to be changed from LH to RH hinged or vice versa	Х	Х	_

general specifications

Access	Front	
Application	150mm and 300mm doors installed on FlexCore™ Vertical Cable Managers. 600mm door installed on FlexCore™ Frame	
Color	Gray or Black	
Mounting	Respective vertical cable managers	

material specifications

Finish	Powder coated
Material type	Steel

environmental specifications

	•
Environment	Indoor
Standards	RoHS

dimensions

	FDUFD1545S*GY	FDUFD3045*GY	FDUFD6045P*GY	
	150mm	300mm	600mm	
Height	83.21" (2113.5mm)	83.21" (2113.5mm)	83.37" (2117.6mm)	
Width	5.69" (144.6mm)	11.58" (294.1mm)	23.41" (594.7mm)	
Depth	1.96" (49.8mm)	1.96" (49.8mm)	2.05" (52.1mm)	
Increases frame depth by	1" (25mm)	1" (25mm)	1.6" (40.6mm)	

^{*} L for Left Hinged, R for Right Hinged

Note: For part number in black, replace GY with BL

WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT US/CANADA Phone: 800.777.3300 PANDUIT EUROPE LTD. London, UK Phone: 44.20.8601.7200 PANDUIT SINGAPORE PTE. LTD. Republic of Singapore Phone: 65.6305.7575 PANDUIT JAPAN Tokyo, Japan Phone: 81.3.6863.6000 PANDUIT LATIN AMERICA Guadalajara, Mexico Phone: 52.33.3777.6000 PANDUIT AUSTRALIA PTY. LTD. Victoria, Australia Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to www.panduit.com/warranty

