


Isometric View

Reference:

1. Material: See chart
2. Material color: See chart
3. Min. Vertical Pull Force: 22N (5 lbf)
4. Maximum percent regrind permissible: 10%
5. Maximum allowable flash to be: 0.25mm
6. Magnets are very strong. Handling them with care is necessary to prevent personal injuries, property damages and magnet damages

 UL Listing		
ANSI/UL 62275	Positioning Devices TYPE 21 E64139	22N (5 lbf) Vertical Pull
CAN	CSA-C22.2 No. 62275	
All testing performed using 3mm min. thick 1008-1010 steel plate		

Global Part Description	Item No.	Qty.	Material	Finish	Color
MAGCTM5M-NDFEB35/POM/ST-BK	1	1	POM	-	Black
	2	1	NdFeB N35M	NiCuNi	Silver
		1	Steel	Zinc Coating	

Revision level			Revision Record	
Drawing	State	Part	ECN 017476 - Initial Release	
00.3	Design Release	-		
Changed	Date (YYYY/MM/DD)			
Johnson	2023/04/03			
Approved	Date (YYYY/MM/DD)			
Toll	2023/04/14			

The copyright of this drawing is reserved by HellermannTyton.

All drawing revision are stored in CAD PDM database

Drawn: Johnson, Date: 2023/04/03

Approved: Toll, Date: 2023/04/14

HellermannTyton
www.HellermannTyton.com

Title: Magnetic Cable Tie Mount Mini, 5 lbf pull rate

Scale: 4:1

Global Project Number: 23-0062

Format: A3

Sheet: 1/1

Drawing-No: 23-0062-001-CSU