

OVERCOAT PEN—CLEAR

419D-P-CL

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Identifier: Overcoat Pen—Clear**Other Means Of Identification:** Stylo de Vernis d'Épargne—Clair**Related Part #** 419D-P-CL

Recommended Use and Restriction on Use

Use: Protective coating for printed circuit boards**Uses Advised Against:** Not available

Details of Manufacturer or Importer

ManufacturerMG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADAMG Chemicals (Head Office)
9347-193 Street
Surrey, British Columbia V4N 4E7
CANADA**TEL** +1-800-340-0772**FAX** +1-800-340-0773**E-MAIL** support@mgchemicals.com**WEB** www.mgchemicals.com**TEL** +1-905-331-1396**FAX** +1-905-331-2682**E-MAIL** info@mgchemicals.com**E-MAIL** (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**

(Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 serviceCANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones

OVERCOAT PEN—CLEAR

419D-P-CL

Section 2: Hazard(s) Identification



Classification of Hazardous Chemical

GHS Categories

Criteria		Category	Signal Word	Pictograms
Flammable Liquid		2	Danger	Flame
Sensitization	Skin	1	Warning	Exclamation
Eye Irritation		2	Warning	Exclamation
Specific Target Organ Toxicity	Single Exposure	3	Warning	Exclamation
Hazardous to the Aquatic Environment	Acute	3	<i>none</i>	<i>none</i>

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
	H225: Highly flammable liquid and vapor
	H317: May cause an allergic skin irritation H319: Causes serious eye irritation H336: May cause drowsiness or dizziness
<i>No Symbol Mandated</i>	H402: Harmful to aquatic life

Section continued on the next page

OVERCOAT PEN—CLEAR
419D-P-CL

Continued...

Prevention	Precautionary Statements
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, flames, and other ignition sources. No Smoking.
P261 + P271	Avoid breathing vapors. Use only outdoors or in a well-ventilated area.
P233	Keep container tightly closed.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/eye protection.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
Prevention	Precautionary Statements
P370 + P378	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
P303 + P361 + P364 + P352	IF ON SKIN (or hair): Take off immediately all contaminated clothing and wash it before reuse. Wash with plenty of water.
P333 + P313	If skin irritation or rash occurs: Get medical advice.
P304 + P340, P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE or doctor if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice.
Storage	Precautionary Statements
P403 + P235	Store in well-ventilated place. Keep cool.
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents in accordance to local, regional, national and international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Skin Dryness	Repeated exposure may cause skin dryness or cracking.	none	none

OVERCOAT PEN—CLEAR
419D-P-CL
Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
123-86-4	n-butyl acetate	59%
78-93-3	butan-2-one ^{a)}	14%
80-62-6	methyl methacrylate	0.1%
97-88-1	n-butyl methacrylate	0.1%

a) Also known as methyl ethyl ketone (MEK)

Section 4: First-Aid Measures

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
IF ON SKIN (or hair)	P303 + P361 + P352, P333 + P313, P363
Immediate Symptoms	<i>redness, irritation, dry skin</i>
Response	Take off immediately all contaminated clothing. Wash with plenty of water or shower. If skin irritation or rash occurs: Get medical advice. Wash contaminated clothing before reuse.
IF INHALED	P304 + P340, P312
Immediate Symptoms	<i>dizziness, drowsiness, cough, headaches, sore throat, nausea</i>
Response	Remove person to fresh air and keep comfortable for breathing. If you feel unwell: Call a doctor.
IF IN EYES	P305 + P351 + P338, P337 + P313
Immediate Symptoms	<i>redness, irritation, pain</i>
Response	Rinse cautiously with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.
IF SWALLOWED	P301 + P330, P331
Immediate Symptoms	<i>nausea, sore throat, diarrhea, drowsiness, dizziness, vomiting</i>
Response	Rinse mouth. Do NOT induce vomiting.

OVERCOAT PEN—CLEAR**419D-P-CL****Section 5: Fire-Fighting Measures**

Extinguishing Media	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
Specific Hazards	The liquid may float on water and ignite. The vapors are heavier than air and may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion.
Combustion Products	Produces carbon oxides (CO,CO ₂)
Fire-Fighter	Wear self-contained breathing apparatus and full fire fighting turn-out gear.

Section 6: Accidental Release Measures

Personal Protection	See personal protection recommendations in Section 8.
Precautions for Response	Avoid breathing the vapors. Remove or keep away all sources of extreme heat or open flames.
Environmental Precautions	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
Containment Methods	Not applicable
Cleaning Methods	Collect liquid in a sealable, solvent-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces of residue.
Disposal Methods	Dispose of spill waste according to Section 13.

OVERCOAT PEN—CLEAR

419D-P-CL

Section 7: Handling and Storage

- Prevention** Keep out of reach of children.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Keep container tightly closed. Avoid breathing vapors. Use only outdoors or in a well-ventilated area.
- Handling** Wear protective gloves and eye protection.
- Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace.
- Wash hands thoroughly after handling.
- Avoid release to the environment.
- Storage** Store in well-ventilated place. Keep cool.
- Store locked up.

Section 8: Exposure Controls/Personal Protection

Summary of Effects and Symptoms by Routes of Exposure

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
n-butyl acetate	ACGIH	150 ppm	Not established
	U.S.A. OSHA PEL	150 ppm	Not established
	Canada AB	150 ppm	200 ppm
	Canada BC	20 ppm	200 ppm
	Canada ON	150 ppm	Not established
	Canada QC	150 ppm	200 ppm
butan-2-one	ACGIH	200 ppm	125 ppm
	U.S.A. OSHA PEL	200 ppm	300 ppm
	Canada AB	200 ppm	300 ppm
	Canada BC	50 ppm	100 ppm
	Canada ON	200 ppm	300 ppm
	Canada QC	150 ppm	300 ppm

Section continued on the next page

OVERCOAT PEN—CLEAR
419D-P-CL
Continued...

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
methyl methacrylate	ACGIH	50 ppm ^{a)}	100 ppm
	U.S.A. OSHA PEL	100 ppm	Not established
	Canada AB	50 ppm	100 ppm
	Canada BC	50 ppm ^{a)}	100 ppm
	Canada ON	50 ppm	100 ppm
	Canada QC	100 ppm	Not established
n-butyl methacrylate	ACGIH	Not established	Not established
	U.S.A. OSHA PEL	Not established	Not established
	Canada AB	Not established	Not established
	Canada BC	50 ppm	Not established
	Canada ON	Not established	Not established
	Canada QC	Not established	Not established

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from by RTECS database² of the Canadian Centre for Occupational Health and Safety (CCOHS) a data from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) Sensitizer (S)

Engineering Controls
Ventilation

Keep airborne concentrations below the occupational exposure limits (OEL).

Personal Protective Equipment
Eye protection

Wear appropriate protective eyeglasses or chemical safety goggles.

RECOMMENDATION: Ensure that glasses have side shields for lateral protection.

Skin Protection

For likely contacts, use of protective butyl rubber or other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant gloves.

Section continued on the next page

OVERCOAT PEN—CLEAR
419D-P-CL

Respiratory Protection For over-exposures up to 10 x OEL of vapors, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit ^{c)}	1.8%
Appearance	Clear	Upper Flammability Limit ^{c)}	9.0%
Odor	Fruity	Vapor Pressure @20 °C ^{c)}	40 hPa [31 mmHg]
Odor Threshold	0.007 ppm	Vapor Density	>2.5 (Air =1)
pH	Not available	Relative Density @25 °C	0.93
Freezing/Melting Point	Not available	Solubility in Water	Slightly soluble
Initial Boiling Point ^{a)}	≥80 °C [≥176 °F]	Partition Coefficient n-octanol/water	Not available
Flash Point ^{a), b)}	-3 °C [26.6 °F]	Auto-ignition Temperature ^{d)}	≥294 °C [≥561 °F]
Evaporation Rate	<1 (ButAc = 1)	Decomposition Temperature	Not available
Flammability	Highly Flammable	Viscosity @25 °C	110 mm ² /s

a) Values based on butan-2-one component.

b) Pensky-Martens closed cup

c) Calculated based on components.

d) Values based on n-butyl methacrylate, which is the component with the lowest auto-ignition value.

OVERCOAT PEN—CLEAR
419D-P-CL
Section 10: Stability and Reactivity

Reactivity	Not available
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Ignition sources, open flames, and incompatible substances
Incompatibilities	Strong oxidizing agents, strong acids
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

Section 11: Toxicological Information
Summary of Effects and Symptoms by Routes of Exposure

Eyes	Causes redness, severe irritation, or pain.
Skin	Causes skin redness, irritation, dry skin, and rashes.
Inhalation	May cause dizziness, drowsiness, cough, headaches, or nausea.
Ingestion	May cause nausea, sore throat, diarrhea, or vomiting.
Chronic	Prolonged or repeated exposure may cause skin dryness, cracking, as well as defatting the skin. May also cause skin allergies.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
n-butyl acetate	>10 768 mg/kg Rat	>17 600 mg/kg Rabbit	390 ppm 4 h Rat
butan-2-one	2 737 mg/kg Rat	6 480 mg/kg Rabbit	23 500 mg/m ³ 8 h Rat
methyl methacrylate	7 872 mg/kg Rat	>5 000 mg/kg Rabbit	78 000 mg/m ³ 4 h Rat
n-butyl methacrylate	16 000 mg/kg Rat	113 000 µL/kg Rabbit	29.8 mg/L 4 h Rat

Note: Toxicity data from the RTECS² and ECHA databases were consulted. The data from supplier SDS were also consulted.

Section continued on the next page

OVERCOAT PEN—CLEAR**419D-P-CL****Other Toxicological Effects**

Skin corrosion/irritation	Based on available data, the classification criteria are not met.
Serious eye damage/irritation	Butan-2-one is a known serious eye irritant.
Sensitization (allergic reactions)	The methyl methacrylate and n-butyl methacrylate may cause skin sensitization according to animal studies.
Carcinogenicity (risk of cancer)	None of the ingredients are classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.
Mutagenicity (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
Reproductive Toxicity (risk to sex functions)	Based on available data, the classification criteria are not met.
Teratogenicity (risk of fetus malformation)	Based on available data, the classification criteria are not met.
STOT-single exposure	The n-butyl acetate, butan-2-one, methyl methacrylate, and n-butyl methacrylate components can affect the central nervous system by inhalation causing drowsiness or dizziness.
STOT-repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met. Contains less than 10% components of category 1, and the mixture has a kinematic viscosity of >20.5 mm ² /s at 40 °C.

OVERCOAT PEN—CLEAR**419D-P-CL****Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

The n-butyl acetate ingredient is hazardous to the aquatic environment with an acute category 3 environmental classification. It is biodegradable, with minimal LC50 of 18 mg/L for Pimephales promelas (fathead minnow).

Based on available data, 2-butanone (MEK) ingredient is not classified as an environmental hazard according to GHS criteria.

The 1-methoxy-2-propanol acetate component is hazardous to the aquatic environment with an acute category 3 classification with minimal LC50 96 h of ≥ 100 mg/L for Salmo gairdneri.

Acute Ecotoxicity

Category 3

Harmful to aquatic life

Avoid release to the environment.

Chronic Ecotoxicity

Available toxicity data does not meet classification thresholds.

Biodegradability

Expected to be biodegradable. The volatile solvent constituents will oxidize rapidly in air by photochemical reaction.

Other Effects

Regulated Volatile Organic Compounds (VOC) content according to the US (EPA) and Canadian (CEPA) authorities.

VOC = 73% [679 g/L]

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

OVERCOAT PEN—CLEAR

419D-P-CL

Section 14: Transport Information

Ground

Refer to TDG (Canadian Transportation of Dangerous Goods regulations) and **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

Sizes 30 mL and under

419D-P-CL

Excepted Quantity

Code **E2**



Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Sizes 30 mL and under

419D-P-CL

Excepted Quantity

Code **E2**

On air waybill, write:
"Dangerous Goods in
Excepted Quantities".



FOR REFERENCE ONLY

UN number: UN1263

Shipping Name: PAINT

Class: 3

Packing Group: II

Marine Pollutant: No

Sea

Refer to IMDG regulations.

Sizes 30 mL and under


419D-P-CL

Excepted Quantity

Document as class **E2**

In transport document,
write:

"Dangerous Goods in
Excepted Quantities".



FOR REFERENCE ONLY

UN number: UN1263

Shipping Name: PAINT

Class: 3

Packing Group: II

Marine Pollutant: No

Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

OVERCOAT PEN—CLEAR

419D-P-CL

Section 15: Regulatory Information

Canada

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.


USA

Other Classifications

HMIS® RATING

HEALTH:	* 2
FLAMMABILITY:	3
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product contains methyl methacrylate, which is listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains n-butyl acetate (CAS# 123-86-4) and 2-butanone (CAS# 78-93-3), which are subject to the CERCLA reporting requirements at the 5 000 lb (2268 kg) threshold.

This product contains 0.1% methyl methacrylate (CAS No 80-62-6), which is subject to CERCLA reporting requirements at a threshold of 1000 lbs (454 kg).

Section continued on the next page

OVERCOAT PEN—CLEAR**419D-P-CL****TSCA** (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity)

This product does not contain any substances known to be listed in California.

Europe**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

Section 16: Other Information

Prepared by the	Regulatory Affairs Department
Date of Revision	27 February 2020
Supersedes	07 November 2018
Reason for Changes:	Update to the emergency contact information and general revision.

Reference

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Section continued on the next page

OVERCOAT PEN—CLEAR**419D-P-CL****Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Phone: +1-905-331-1396

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Head Office
9347–193rd Street
Surrey, British Columbia, Canada
V4N 4E7

Disclaimer

This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.