



American Electrical, Inc.

Industrial Electrical Components

AEI Part Numbers		CC18-110	CC22-110	CC40-110	CC50-110	CC65-110	CC85-110	CC100-110
		CC18-230	CC22-230	CC40-230	CC50-230	CC65-230	CC85-230	CC100-230
		CDC18-24	CDC22-24	CDC40-24	CDC50-24	CDC65-24	CDC85-24	CDC100-24
		CDC18-12	CDC22-12	CDC40-12	CDC50-12	CDC65-12	CDC85-12	CDC100-12
Continuous Current		32	40	60	70	100	135	160
1pH (HP)	110-130 VAC	1	2	3	3	5	7.5	10
	220-240 VAC	3	3	7.5	10	15	15	20
3pH (HP)	200-208 VAC	5	7.5	15	20	25	30	30
	220-240 VAC	7.5	10	15	25	30	40	40
	400-480 VAC	10	15	30	40	50	60	75
	550-600 VAC	15	20	30	50	60	75	75
Wire Range (AWG)		16-8	14-8	8-6	10-4	8-3	8-1/O	8-2/O
Wire Type		Stranded	Stranded	Stranded Solid	Stranded Solid	Stranded Solid	Stranded Solid	Stranded Solid
Torqu (lb-in)		20	20	35	35	45	45	4