

	1	2	3	4	5	6	7	
--	---	---	---	---	---	---	---	--

**NOTES:**  
 Plunger: Brass, 20μ" MIN Au over, 50μ" MIN Ni over  
 Barrel : Brass, 3μ" ,MIN Au over, 50μ" MIN Ni over  
 Spring : Stainless Steel

**Mechanical Characteristics:**  
 Spring Force : 60g ± 20% at Working Length  
 Mechanical Life : 1,000,000 cycle

**Electrical Characteristics:**  
 Current Rating : 2A  
 Contact Resistance : 20 mΩ Max

Operating Temperature range : -55~125° C  
 Packing: PE Bag

G	<b>RoHS compliant</b> Unit: mm		Scale	Free					Date	Name	Customer-No.
			TOLERANCE					Drawn	28.03.2018	Tom	
	X.X	±0.20					Approved	28.03.2018	Winnie	ASSMANN WSW-No.	
	X.XX	±0.10								A-CSL-S-020-B2	
H	X.XXX	±0.08								Drawing-No.	
	DIM	TOL					<b>ASSMANN</b> WSW components		ASS 7893 CO	rev00	
	Angle	±3°	ⓐ	Drawn	28.03.2018	Tom			Replace	Sheet	
Angle	TOL	Id.	Modification	Date	Name						

	1	2	3	4	5	6	7	SV4444
--	---	---	---	---	---	---	---	--------