



## HM-RS232-ISO HART® Modem - RS232 Electrically Isolated



### Features:

- 1500 Vdc Opto Isolation between HART and RS232 circuits
- Integral standard RS-232 female connector
- Integral heavy duty HART Minigrabber connectors
- Designed to meet HART Physical Layer Spec HCF\_SPEC-54
- Self powered, no external power supply or batteries needed
- 48" (1.2m) cable length
- No driver installation necessary
- Compact size 2.75" x 2.0" x 0.8" (70mm x 51mm x 20mm)
- Rugged ABS plastic enclosure
- Custom cable lengths available
- HART Modem Test Program included
- HART Foundation Registered, Registration Number L2-06-1000-305
- CE certified
- Cost effective
- Each unit 100% tested
- 1 Year warranty



## Specifications:

### Enclosure

Material	High strength ABS Plastic
Dimensions	2.75" x 2.0" x 0.8" (70mm x 51mm x 20mm)
Total Unit Weight	4.8 oz (136 g)

### Cables

HART Cable Length	4' (1.2 m)
HART Cable Connectors	Mini-Grabber
RS232 Cable Length	18" (0.5 m)
Cable Connector	RS232 Female

### HART

Interface	Capacitive and transformer coupling
Output	600 mVpp
Leakage	< 10 uA
Isolation Voltage	1500 Vdc
Connections	Across loop resistor or HART field device
Specifications	HART 4, HART 5, HART 6, HART 7, HART Physical Layer Spec HCF_SPEC-54
HART Foundation	Registration Number L2-06-1000-305

### Computer

Operating System	Windows 7 and higher
------------------	----------------------

### RS232

Power	RS232 port provides power to unit
Current Draw	17mA

### Environmental

Operating Temperature	0 degC to 50 degC (32 degF to 122 degF)
Storage Temperature	-40 degC to 85 degC (-40 degF to 185 degF)
Humidity	0% to 99% (non-condensing)

### Compliances

CE Certification	EN 61326 (EMC), Directive 2011/65/EU (RoHS)
------------------	---

**ProComSol, Ltd**  
*Process Communications Solutions*

Phone: 216.221.1550  
Toll Free: 877.221.1551  
Email: [sales@procomsol.com](mailto:sales@procomsol.com)  
Web: [www.procomsol.com](http://www.procomsol.com)