

Part Number: 2196772102

Product Description : Pre-Crimped Lead Mini-SPOX Female-to-Pigtail, Tin (Sn) Plating,

150.00mm Length, 26 AWG, Red

Status: Active

Series Number: 219677

Product Category : Power and Signal Cable Assemblies

Documents & Resources

Drawings

Drawing 2196772102_sd.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|---|
| China RoHS | © |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2- 21 |
| REACH SVHC | Not Contained per D(2023)8585-DC (23 Jan 2024) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|------------------------|--|
| Category | Power and Signal Cable Assemblies |
| Series | 219677 |
| Description | Pre-Crimped Lead Mini-SPOX Female-to-Pigtail, Tin (Sn) Plating, 150.00mm Length, 26 AWG, Red |
| Application | Signal, Wire-to-Board |
| Assembly Configuration | Pre-crimped Lead Only |
| Connector to Connector | Mini-SPOX-to-Pigtail |
| Product Family | Off-the-Shelf Pre-Crimped Leads |
| Product Name | Mini-SPOX |
| UPC | 195842853409 |

Electrical

| Current - Maximum per Contact | 2.0A |
|-------------------------------|------------------|
| Voltage - Maximum | 250V AC (RMS)/DC |

Physical

| Cable Length | 150.00mm |
|--------------------------------|----------------------|
| Circuits (Loaded) | 1 |
| Circuits (maximum) | 1 |
| Color - Resin | Red |
| Gender | Female-Pigtail |
| Material - Metal | Phosphor Bronze |
| Material - Plating Mating | Tin |
| Material - Plating Termination | Tin |
| Material - Resin | PVC |
| Net Weight | 0.513/g |
| Number of Rows | 1 |
| Packaging Type | Bag |
| Plating min - Mating | 0.889µm |
| Plating min - Termination | 0.914µm |
| Single Ended | Yes |
| Termination Interface Style | Crimp or Compression |

| Wire/Cable Type | UL 1569 |
|--------------------------|-------------|
| Wire Insulation Diameter | 1.90mm max. |
| Wire Size (AWG) | 26 |

Use with Part(s)

| Description | Part Number |
|---|-------------|
| Mini-SPOX Single Row Receptacle Housings | <u>5264</u> |

This document was generated on Apr 13, 2024