

Magnets

NVE offers several popular permanent magnets for use with magnetic sensors. In addition to individual magnets, NVE offers evaluation kits containing assortments of magnets, magnetic sensors, and printed circuit boards for sensor system development.


The following magnets are available:




NVE Part No.	Description	Dimensions	Typ. Field at Face	Evaluation Kits
12030	Ferrite Bar Magnet	0.5" L x 0.125" W x 0.25" T	150 mT	AG001-01, AG040, AG940, and others
12031	Ferrite Disk Magnet	0.312" dia. x 0.125" thick	90 mT	AG001-01
12032	Ferrite Bar Magnet	1" L x 0.125" W x 0.39" T	180 mT	AG910-07; AG911-07
12216	Ferrite Disk Magnet	6 mm dia. x 4 mm thick	110 mT	AG920-07
12217	Ferrite Disk Magnet	3.5 mm dia. x 4 mm thick	170 mT	AG920-07
12249 12526 12527 12528	Diametrically-Magnetized Disk Magnets	12 mm dia. x 4 mm thick 4 mm dia. x 4 mm thick 8 mm dia. x 4 mm thick 8 mm dia. x 8 mm thick	100 mT 80 mT 90 mT 100 mT	None (compatible with AAT/ADT/ADT/ASR-Series sensors)
12426	Alnico-5 Split-Pole Round Horseshoe	0.44" dia. x 0.44" H (see fig.)	110 mT	AAT/ADT/ADT/ASR-Series angle sensors

Use our [Web application calculators](http://www.nve.com/spec/calculators.php) (www.nve.com/spec/calculators.php) to estimate the magnet fields at various distances.


Disc Magnets (C5, Y25, or similar)




Bar Magnets (C1, Y10T, C5, Y25, or similar)



12249, 12526, 12527, and 12528 Diametrically-Magnetized Magnets (C5, Y25, or similar)



12426 Split-Pole Round Horseshoe Magnet (Alnico 5)




Magnet Material Specifications


	C1/Y10T	C5/Y25	Alnico-5
Maximum Operating Temperature	300°C	300°C	525°C
Curie Temperature	450°C	450°C	860°C
Temperature Coefficient of Flux Density	-0.20%/°C	-0.20%/°C	-0.02%/°C
Maximum Energy Product	1 MGOe	3.4 MGOe	5.5 MGOe
Residual Induction	2175 Gauss	3800 Gauss	12800 Gauss
Coercive Force	1800 Oe	2400 Oe	640 Oe

Material Characteristics


C1/Y10T Magnetic Characteristics



C5/Y25 Magnetic Characteristics



Alnico-5 Magnetic Characteristics



Datasheet Limitations

The information and data provided in datasheets shall define the specification of the product as agreed between NVE and its customer, unless NVE and customer have explicitly agreed otherwise in writing. All specifications are based on NVE test protocols. In no event however, shall an agreement be valid in which the NVE product is deemed to offer functions and qualities beyond those described in the datasheet.

Limited Warranty and Liability

Information in this document is believed to be accurate and reliable. However, NVE does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

In no event shall NVE be liable for any indirect, incidental, punitive, special or consequential damages (including, without limitation, lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Right to Make Changes

NVE reserves the right to make changes to information published in this document including, without limitation, specifications and product descriptions at any time and without notice. This document supersedes and replaces all information supplied prior to its publication.

Use in Life-Critical or Safety-Critical Applications

Unless NVE and a customer explicitly agree otherwise in writing, NVE products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical devices or equipment. NVE accepts no liability for inclusion or use of NVE products in such applications and such inclusion or use is at the customer's own risk. Should the customer use NVE products for such application whether authorized by NVE or not, the customer shall indemnify and hold NVE harmless against all claims and damages.

Applications

Applications described in this datasheet are illustrative only. NVE makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using NVE products, and NVE accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the NVE product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customers. Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

NVE does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customers. The customer is responsible for all necessary testing for the customer's applications and products using NVE products in order to avoid a default of the applications and the products or of the application or use by customer's third party customers. NVE accepts no liability in this respect.

Limiting Values

Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and operation of the device at these or any other conditions above those given in the recommended operating conditions of the datasheet is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

Terms and Conditions of Sale

In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. NVE hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of NVE products by customer.

No Offer to Sell or License

Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export Control

This document as well as the items described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.

Automotive Qualified Products

Unless the datasheet expressly states that a specific NVE product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. NVE accepts no liability for inclusion or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without NVE's warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond NVE's specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies NVE for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond NVE's standard warranty and NVE's product specifications.

©NVE Corporation

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

SB-00-019

April 2020