


General Specifications:
 Operating Voltage : 5-250V
 Current : 3A DC, 16A AC
 Panel thickness range : 0.04"-0.2" (1~5mm)
 Operation Cycles (nominal) : > 1m
 Material : ABS-PC UL 94 V0

Designed for snap-in, nut-less installation

RDI PN- VPS-B16-XXX-X1-NL

[XXX= Operating force: 100gf, 150gf, 200gf, 250gf, 300gf]
 [X1= Button color: B= Black, R= Red, G= Green, Y=Yellow]

NOTE: ALL DIMS ARE IN mm

PROJECTION		 Research Develop Innovate RDI, Inc. 333 North Bedford Road, Suite 135, Mount Kisco, NY 10549	
SCALE N/A		TITLE Multi-purpose panel mount pushbutton switch, RoHS Compliant	
TOLERANCE		DR. Tina	DATE 03/24/23
>0.5-6 ±0.10 6-30 ±0.20 30-120 ±0.30		REF. PART NO. VPS-B16-XXX-X1-NL	SHEET 1 OF 1
DEC. MILLIMETERS ±0.5		CK. BM	REV. -
ANG. N/A		PRE-SW	DRAWING NO. 5354
THIS DOCUMENT IS OWNED BY, AND THE INFORMATION CONTAINED IN IT IS PROPRIETARY TO, RDI, BY RECEIPT HEREOF THE HOLDER AGREES NOT TO USE THE INFORMATION AND NOT TO DISCLOSE IT TO ANY THIRD PARTY, NOR REPRODUCE THIS DOCUMENT WITHOUT THE WRITTEN CONSENT OF RDI, AND AGREES TO RETURN THIS DOCUMENT FORTHWITH UPON REQUEST.			

ECN#	DATE	SYM	REVISION RECORD	AUTH	BY
------	------	-----	-----------------	------	----