



Precision Calibrated, Output Isolator
WR-28 Waveguide Noise Source Module, Output
ENR of 15 dB, +28 VDC, 26.5 GHz to 40 GHz

Noise Generators Technical Data Sheet

PEWNS2000

Features

- WR-28 Waveguide Noise Source with Output Isolator
- Q Band Frequency Range: 26.5 GHz to 40 GHz
- Output ENR Level: 15 dB min
- Noise Output Variation: < 0.01 dB/°C , < 0.1 dB/%V
- Flatness +/- 0.75 dB max
- DC Voltage: +28 Vdc
- 0°C to +85°C Operating Temperature
- VSWR: 1.3:1 Max

Applications

- Noise Figure Test & Measurement
- Built-In Test Applications
- Laboratory Applications
- mm-Wave Radiometers
- Automotive Radar
- R&D for Broadband mm-Wave
- Wireless Communication Systems

Description

The PEWNS2000 is a Ka Band waveguide Noise Source module with output Isolator that operates over the full frequency range of 26.5 GHz to 40 GHz. The benefit of the output Isolator results in improved output port matching for more accurate measurements as well as protection of the noise diode from incident RF power. The microstrip assembly incorporates a millimeter wave noise diode screened for superior noise characteristics that results in highly stable and reliable performance. This module can be used in built-in test and laboratory applications, and can replace outdated gas tube noise sources. Additional applications include noise figure measurements, millimeter wave radiometers, automotive radar, and research and development in mm-wave broadband wireless communication systems. The design operates at +28 Vdc with an output ENR level of 15 dB min and a noise output variation of < 0.01 dB/°C, < 0.1 dB/%V. Maximum Flatness across the frequency band is +/- 0.75 dB and output VSWR is 1.3:1 with the Isolator. Operating temperature range is 0°C to +85°C. The rugged package supports a WR-28 waveguide interface and a BNC connector for the DC voltage supply.

Electrical Specifications

RF Characteristics

Description	Minimum	Typical	Maximum	Units
Frequency Range	26.5		40	GHz
Impedance		50		Ohms
Output ENR	15			dB
Flatness			±0.75	dB
VSWR			1.3:1	
Output Variation vs Input Voltage			0.1	dB/%V
Output Variation vs Temperature			0.01	dB/deg C
Bias Voltage 1		28		Volts
Input Current 1			30	mA

Mechanical Specifications

Package Type

Connectorized Module

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Precision Calibrated, Output Isolator WR-28 Waveguide Noise Source Module, Output ENR of 15 dB, +28 VDC, 26.5 GHz to 40 GHz PEWNS2000](#)



Precision Calibrated, Output Isolator
WR-28 Waveguide Noise Source Module, Output
ENR of 15 dB, +28 VDC, 26.5 GHz to 40 GHz

Noise Generators Technical Data Sheet

PEWNS2000

Connectors

DC Connector

BNC

Environmental Specifications

Temperature

Operating Range


0 to +85 °C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Typical Performance Data



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Precision Calibrated, Output Isolator WR-28 Waveguide Noise Source Module, Output ENR of 15 dB, +28 VDC, 26.5 GHz to 40 GHz PEWNS2000](#)



Precision Calibrated, Output Isolator
WR-28 Waveguide Noise Source Module, Output
ENR of 15 dB, +28 VDC, 26.5 GHz to 40 GHz

Noise Generators Technical Data Sheet

PEWNS2000

Precision Calibrated, Output Isolator WR-28 Waveguide Noise Source Module, Output ENR of 15 dB, +28 VDC, 26.5 GHz to 40 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Precision Calibrated, Output Isolator WR-28 Waveguide Noise Source Module, Output ENR of 15 dB, +28 VDC, 26.5 GHz to 40 GHz PEWNS2000](https://www.pasternack.com/precision-calibrated-output-isolator-noise-source-enr-15-db-40-ghz-pewns2000-p.aspx)


URL: <https://www.pasternack.com/precision-calibrated-output-isolator-noise-source-enr-15-db-40-ghz-pewns2000-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PEWNS2000 CAD Drawing

Precision Calibrated, Output Isolator WR-28 Waveguide Noise Source Module, Output ENR of 15 dB, +28 VDC, 26.5 GHz to 40 GHz

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	02/19/2020	TGALLA



<p>PE PASTERNAK an INFINITI brand</p> <p>Pasternack Enterprises, Inc. P. O. Box 16759, Irvine, CA 92623. Phone: 1.949.261.1920 1.866.727.8376 Fax: 1.949.261.7451 Website: www.pasternack.com E-mail: sales@pasternack.com</p>	<p>THIRD-ANGLE PROJECTION</p> <p>THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF PASTERNAK CORPORATION ALL RIGHTS RESERVED.</p> <p>SHEET 1 OF 1</p>
	<p>SCALE N/A</p>
<p>SIZE A</p> <p>CAGE CODE 53919</p> <p>DRAWN BY DZINN</p> <p>ITEM NO. PEWNS2000</p>	<p>REV A</p>

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:

.X = ±.2	[.008]	FRACTIONS	± 1/32
.XX = ±.02	[.51]	ANGLES	± 1°
.XXX = ±.005	[.13]	CABLE LENGTH (L), TOLERANCES:	

L ≤ 12 [305] = +1 [25] / -0
 12 [305] < L ≤ 60 [1524] = +2 [51] / -0
 60 [1524] < L ≤ 120 [3048] = +4 [102] / -0
 120 [3048] < L ≤ 300 [7620] = +6 [152] / -0
 300 [7620] < L = +5% / -0

ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.