

Specification

Model	YSIMXXX-S320			
Dimensions	mSATA, L50.95mm * W30.0mm * H3.5mm Error±0.15mm			
Interface	mSATA 52PIN			
Protocol	SATA III (6Gb/s)- with backwards compatibility to SATA II (3Gb/s)			
Supported Systems	Windows 7,Windows 8,Windows 10,Windows Server 2012 R2,RHEL, CentOS,Ubuntu,Linux			
Capacity	32GB	64GB	128GB	256GB
NAND Flash	MLC	MLC	MLC	MLC
Sequential Read (MB/s)	280~350	300~350	400~450	450~500
Sequential Write (MB/s)	50~100	150~200	200~250	300~350
TBW	90TB	185TB	375TB	750TB
4K Random read(IOPS)	48100(Max)			
4K Random write(IOPS)	55360(Max)			
Input voltage	DC 3.3V±5%			
Power consumption Idle	0.32W(Max)			
Power consumption Active	2.47W(Max)			
Data retention	10 years below 25 degree			
MTBF	2 million hours			
ECC	Hardware BCH ECC capable of correcting errors up to 66-bit/1KB			
Features	System automatic bad block management			
Operating Temp.	0°C~70°C			
Storage Temp.	-40°C ~ 85°C			
Humidity	5-95%			



Shenzhen KingSpec Electronics Technology Co., Ltd.

Phone: 0755-26985321

URL: www.yansen-ssd.com

Office: 2001, Block C, Minzhi Joint Stock Commercial Center, North Station Community, Minzhi Street, Longhua District, Shenzhen, China, 518000