



Cross-connector, No. of poles: 2, Mounting type: Can be screwed on, Width: 34.3 mm, Rated cross-section: 70 mm², Colour: natural

Business data

Article number	<u>17265.0</u>
Article name	SQ 70/2
GTIN (EAN)	4044211186845
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	37.82 g
Weight per piece (including packaging)	38.1 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Product description	Cross-connector
Colour	Natural



Technical data

Dimensions	
Length	10 mm
Width	34.3 mm
Height	24.5 mm
Hole diameter	5.5 mm
Hole spacing (mid-point to mid-point)	20.5 mm
Pitch size	20.5 mm
Ratings	
Max. voltage	1000 V
Rated current	192 A
Current load, max.	232 A
Rated cross-section	70 mm²
Contamination degree	3
Connection data	
No. of poles	2
Screw head	Slotted
Screw threading	M 6
Tightening torque, min.	3.2 Nm
Tightening torque, max.	3.7 Nm
Materials	
Material	Copper
Surface	Tin-plated
Surface screw	Galvanized
Further technical data	
Mounting type	Screwable
Number of bridged terminals	2
Environmental Product Compliance	
REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes

ZCONTACLIP

Media





Accessories

##INVERSE##CONTA-CONNECT

	•	0
•		0

Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated
cross-section: 70 mm ² , Width: 20.5 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17161.2	SRK 70/2A BG	4044211189273	10



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated
cross-section: 70 mm ² , Width: 20.5 mm, Colour: Black-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
17162.2	SRK 70/2A/PE BKYE	4044211186777	10 ST