


P/N	CABLE LENGTH FT (METERS)
VS2-CABLE-02	2 (.61)
VS2-CABLE-04	4 (1.22)
VS2-CABLE-08	8 (2.44)
VS2-CABLE-16	16 (4.88)
VS2-CABLE-20	20 (7.1)
VS2-CABLE-30	30 (9.15)

NOTES:

1. READ VERISAFE 2.0 INSTRUCTION MANUAL (B21110) BEFORE USING.
2. FOR USE WITH VS2-AVT-\* PART NUMBERS.
3. OPERATING TEMPERATURE: -45°C TO 60°C
4. 600V, HIGH FLEX INDUSTRIAL ETHERNET U/UPT STRANDED WIRE.
5. NOT QUALIFIED TO BE USED AS AN ETHERNET CABLE.

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
0	5/10/22	DFA	ZSG	MSAD	INITIAL RELEASE	GAECN06510

INSPECTION INSTRUCTION NUMBER TITLE		FMEA & CONTROL PLAN NUMBER	
<b>VERISAFE 2.0 SYSTEM CABLE</b>			
CUSTOMER DRAWING			
ITEM REVISION NAME <b>18I216PP/05</b>		<b>PANDUIT</b>	
DATASET FILE NAME <b>18I216PP_DC/05</b>			
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [ mm ]		MATERIAL:  N/A	
.x ± .1 [ 2.54 ]	.xxx ± .005 [ .127 ]	DRAWING NUMBER: <b>18I216PP_DC</b>	
.xx ± .01 [ .25 ]	ANGLES ± 5 °		
 THIRD ANGLE PROJECTION		SCALE	
DRAWN BY <b>DFA</b>	DATE <b>5/10/22</b>	CHK <b>ZSG</b>	SCALE <b>NONE</b>
SHT 1 OF 1		SIZE <b>B</b>	

D10100DB/17