



ISO9001:2008 Certified

Mechanical Specifications (mm)

	D:	7.5	± 1.0
	T:	4.0	± 1.0
	Lead Diameter	0.5	± .1
	S:	5.0	± 1.0
	L:	38.0	± 9
	Coating Lead Run Down (straight Leads)		±
	B:	4.00	± 2
	C:	1.50	± .5



Electrical Specifications

	Resistance:	10.0 Ω	± 20 %
	Max Steady State Current upto 65°C:	3.20	A
	Max Rec. Energy Rating:	9	J
	Actual Failure Instantaneous Energy:	18	J
	Maximum Capacitance @ 120 VAC:	630	µf
	Maximum Capacitance @ 240 VAC:	160	µf
	Resistance @ 100% Max Current:		Ω
	Resistance @ 50% Max Current:		Ω
	Body Temperature at 100% Max Current:	158.00	°c
	Dissipation Constant:	9.0	mw/°c
	Thermal Time Constant:	27	Sec.
	Material Type (for Beta and Curve):	B	

SL08 10003	
Date: 08/23/2012	Drawn by: Erin Landis
Ametherm, Inc. 3111 N. Deer Run Road Carson City, Nevada USA 89701 www.ametherm.com	Approved By: Mehdi Samii
	Revision: A